



RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Use this CMP-rated Multi-Format Runner for in-wall installations that support high density, multi-format applications. Whether hanging a projector in a modern 21st century classroom or installing a commercial digital signage system, a clean, crisp signal will be delivered every time.

For more information on the RapidRun Multi-Format products, click [here](#).

Please note: Each complete RapidRun Multi-Format All-In-One runner solution requires a break-away flying lead or wall plate to terminate with HD15, 3.5mm and 3RCA connections.

Features & Benefits

Supports flexible, high density, multi-format applications

CMP-rated for in-wall installations

Requires a break-away flying lead or wall plate

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120600763	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Cable

Dimensions

Cable Length	10 ft	Outside Diameter	9 mm
--------------	-------	------------------	------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG
Video Resolution	UXGA (1600x1200)	Jacket Application	In-Wall Rated
Bend Radius	90 mm	Cable Type	Audio, Extension, Video
Jacket Rating	CMG Rated, FT4 Rated	Cable Diameter	9 mm
Connector 2	RapidRun 15-pin Female	Connector 1	RapidRun 15-pin Male
Video Output Support	VGA	Video Input Support	VGA