



RapidRun is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Ideal for educational and institutional installations, this wall plate allows PC video, 3.5mm stereo audio and RCA composite audio/video to be run over one Runner cable, while the HDMI pass through allows for a seamless transition to an in-wall HDMI cable. This wall plate is constructed from aluminum for durability and a long life.

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate. Due to constraints of available conductors for signal transmission, EDID signals are not supported with this product.

Features & Benefits

Supports VGA video, Stereo Audio, Composite Video and RCA Stereo Audio signals over a RapidRun Multi-format rRunner Flexible HDMI pigtails for easy installation in a wall box
Compatible with standard double gang wall boxes Aluminum construction for durability and long life

Specifications

General Info

Product Line	C2G	Color	Aluminum
UPC Number	757120601432	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Wall Plate Insert

Listing Agencies / 3rd Party Agencies

CE Certified	Yes
--------------	-----

Technical Information

Wire Gauge	24 AWG	Video Resolution	UXGA (1600x1200)
Number of Ports	7	Number of Gangs	2
Connector 2	RapidRun 15-pin Male	Connector 1	3.5mm Stereo Female, RCA Stereo Audio Female, RCA Composite Video Female, VGA Female
Video Output Support	VGA	Operating Temperature	-25°-80°C
Video Input Support	VGA		