



RapidRun is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Ideal for educational and institutional installations, this wall plate allows VGA video, 3.5mm stereo audio to be run over one runner cable, while the HDMI pass through allows for a seamless transition to an in-wall HDMI cable. This wall plate is constructed from aluminum for durability and a long life.

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate. Due to constraints of available conductors for signal transmission, EDID signals are not supported with this product.

Features & Benefits

Supports VGA video and Stereo Audio signals over a RapidRun Multi-format runner	Flexible HDMI pigtail for easy installation in a wall box
Compatible with standard single gang wall boxes	Aluminum construction for durability and long life

Specifications

General Info

Product Line	C2G	Replaced by Part Number	60171
Color	Aluminum	UPC Number	757120601456
Country Of Origin	Vietnam	Application Sector	Commercial
Type	Wall Plate		

Dimensions

Product Width US	2.76 in	Product Height US	4.53 in
------------------	---------	-------------------	---------

Listing Agencies / 3rd Party Agencies

CE Certified	Yes
--------------	-----

Technical Information

Wire Gauge	24 AWG	Video Resolution	UXGA (1600x1200)
------------	--------	------------------	------------------

Bend Radius	90 mm	Data Transfer Rate	18 Gbps
Connector 2	RapidRun 15-pin Male, HDMI Female	Connector 1	3.5mm Stereo Female, VGA Female, HDMI Female
Video Output Support	VGA	Video Input Support	VGA
