



RapidRun is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Ideal for educational and institutional installations, this wall plate allows VGA video, 3.5mm stereo audio to be run over one runner cable, while the HDMI pass through allows for a seamless transition to an in-wall HDMI cable. This wall plate is constructed from aluminum for durability and a long life.

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate. Due to constraints of available conductors for signal transmission, EDID signals are not supported with this product.

Features & Benefits

| | |
|---|---|
| Supports VGA video and Stereo Audio signals over a RapidRun Multi-format runner | Flexible HDMI pigtail for easy installation in a wall box |
| Compatible with standard single gang wall boxes | Aluminum construction for durability and long life |

Specifications

General Info

| | | | |
|--------------------|--------------|-------------------|------------|
| Product Line | C2G | Color | White |
| UPC Number | 757120601579 | Country Of Origin | China |
| Application Sector | Commercial | Type | Wall Plate |

Technical Information

| | | | |
|----------------------|-----------------------------------|---------------------|--|
| Wire Gauge | 24 AWG | Video Resolution | UXGA (1600x1200) |
| Bend Radius | 90 mm | Data Transfer Rate | 18 Gbps |
| Connector 2 | RapidRun 15-pin Male, HDMI Female | Connector 1 | 3.5mm Stereo Female, VGA Female, HDMI Female |
| Video Output Support | VGA | Video Input Support | VGA |