

RapidRun is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Constructed from aluminum for durability, this wall plate has a locking connector that enables the integrator to save valuable space inside the surface mount or electrical box that typically is already packed with cables.

Ideal for educational and institutional installations, this wall plate sends VGA and Stereo Audio over a single Multi-Format runner cable. It is commonly used on the teacher's station (computer) end of classroom setups with the corresponding flying lead used at the projector.

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate.
 <



Features & Benefits

- Supports VGA video and Stereo Audio signals over a RapidRun Multi-format runner
- Single keystone opening for ethernet or other connection types
- Aluminum construction for durability and long life
- Flexible HDMI pigtail for easy installation in a wall box
- Compatible with standard single gang wall boxes

Specifications

General Info

| | | | |
|--------------------|-------------------------|-------------------|----------------------|
| Product Line | C2G | Color | Aluminum |
| UPC Number | 757120601692 | Country Of Origin | China |
| Application Sector | Residential, Commercial | Type | Wall Plate, Keystone |

Additional Information

| | | | |
|--------------------------|-----|--------------------------|------------------------------|
| Prop 65 Warning Required | Yes | Prop 65 Warning Language | Cancer and Reproductive Harm |
|--------------------------|-----|--------------------------|------------------------------|

Technical Information

| | | | |
|-----------------|--------|------------------|-----------------------------------|
| Wire Gauge | 24 AWG | Video Resolution | UXGA (1600x1200) |
| Number of Gangs | 1 | Adapter Rear | HDMI Female, RapidRun 15-pin Male |

Adapter Front

HDMI Female, VGA Female, 3.5mm
Stereo Female
