



The HDMI Over Cat5/6 Extender is ideal for extending digital video and audio, making it a great solution for digital signs, schools, churches, trade show presentations, or any application where the HDMI source is farther than 50 feet from the display. The extender can also send HDMI signals over existing Cat5 or Cat6 cable infrastructure for cost-effective reliability, while maintaining high performance quality.

Convenience

This solution is able to extend HDMI video and audio up to 164 feet and requires the use of a single Cat5 or Cat6 patch cable. With no drivers or software to install, the HDMI over Cat5/6 Extender provides total plug and play convenience. Simply connect the transmitter to the video source, the receiver to the display, and extend with a single category cable for quality video and audio.

Performance

Supporting resolutions up to 1080p at 60Hz and delivering quality sound allows the HDMI extender to meet the requirements for high performance applications and adds greater functionality to displays.

Features & Benefits

Requires a single Cat5 or Cat6 cable

Supports 1080p and 3D

HDMI transfer rate of 6.75Gbps

International power supply

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120601807	Country Of Origin	China
Application Sector	Commercial, Hospitality	Warranty Type	5-Year
Type	Active Device, Extender		

Dimensions

Product Width US	1.93 in	Product Height US	0.94 in
Product Length US	3.32 in		

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
--------------	-----	---------------	-----

REACH Compliant	Yes
-----------------	-----

Technical Information

Max Distance Support	164 ft	Video Resolution	1080p
----------------------	--------	------------------	-------

Storage Humidity	0-80% RH (Non-Condensing)	Data Transfer Rate	6.75 Gbps
------------------	---------------------------	--------------------	-----------

Connector 2	RJ-45 Female, HDMI Female	Connector 1	RJ-45 Female, HDMI Female
-------------	---------------------------	-------------	---------------------------

Operating Temperature	0°-40°C, 32°-104°F	Operating Humidity	0-80% RH (Non-Condensing)
-----------------------	--------------------	--------------------	---------------------------

Storage Temperature	0° - 40° C, 32° - 104° F
---------------------	--------------------------
