



C2G

3ft (0.9m) C2G Performance Series Ultra Flexible High Speed HDMI™ Cable - 4K 60Hz In-Wall, CMG (FT4) Rated
Part No. CG-C2G10376



C2G Performance Series Ultra Flexible High Speed HDMI™ Cables extend signals over a high-performance HDMI™ cable and support HDMI™ audio and video features including 4K Ultra HD.

These cables are perfect for connecting a wide variety of devices from computers to projectors and monitors, AV presentation furniture, or in-wall applications requiring high speed HDMI™ features and video resolutions up to 4K (4096 x 2160) at 60Hz - perfect for conference rooms, classrooms, houses of worship, and other commercial installations.

This Ultra Flexible High Speed HDMI™ Cable was designed for installations in tight spaces and offers commercial grade connectors that feature compact overmolding for high density environments, integrated finger grips on the top, bottom, and sides, for easy insertion and removal, and the gripping connector shell has 2x greater port retention to keep your devices connected. The gold plated connectors on the cable allow for better shielding, increased electrical conductivity, and durability.

Features & Benefits

Supports output resolutions up to 4K (4096 x 2160) at 60Hz, delivering high-quality video for clear and detailed screen content

Integrated finger grips on the connectors for easy insertion and removal

Gold-plated connectors for increased electrical conductivity and enhanced durability

Backed by a Lifetime Warranty for peace of mind

In-wall (CMG/FT4) rated jacket, so you can safely run the cable inside of a wall and have a clutter-free, clean look

Gripping connector shell for 2x greater port retention

Supports CEC extensions for control of consumer electronics devices through a single control point

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120103769	Country Of Origin	China
Features	Gripping Connectors	Application Sector	Commercial, Residential
Warranty Type	Lifetime	Type	Cable

Dimensions

Product Length US	3.0 FT	Cable Length	3 ft
Outside Diameter	6 mm		

Technical Information

Video Resolution	4K	Jacket Application	In-Wall Rated
Bend Radius	48 mm	Cable Type	High Speed HDMI, Ultra-Flexible, Video
Jacket Rating	CMG Rated, FT4 Rated	Temperature Rating	75° C
Cable Diameter	6 mm	Data Transfer Rate	18 Gbps
Signal	HDMI	Connector 2	HDMI Male

Connector 1	HDMI Male	Video Output Support	HDMI
Operating Temperature	-20°-75°C	Operating Humidity	85% RH (Non-Condensing)
Video Input Support	HDMI	Storage Temperature	-10° - 55° C
