

C2G Performance Series Ultra High Speed HDMI Cables are ideal for computers, game consoles, and displays requiring high bandwidth solutions and video resolutions up to 8K - perfect for high-resolution applications in video production, broadcasting, gaming, and other business and consumer applications.

These Ultra High Speed HDMI Cables support a super immersive viewing experience with resolutions up to 8K, four times as many pixels that 4K offers. Ultra-fast motion images from fast-action videos, gaming, and VR applications are crisp and sharp with the 4K 120hz capability. Other resolutions are also supported, including 5K and 10K for commercial AV, industrial, and specialty usages. The 48Gbps bandwidth allows higher resolutions, faster frame rates, and enhanced audio and media features.



Dynamic HDR optimizes displayed video on a scene-by-scene or even a frame-by-frame basis and provides an extended contrast range providing darker blacks and brighter whites and greater image detail in all color spaces of the image. In addition, enhanced Audio Return Channel (eARC) is supported, an evolution of the previous Audio Return Channel (ARC), which now supports the latest audio formats up to 192kHz, 24-bit, and uncompressed 5.1 and 7.1, and 32-channel uncompressed audio.

The in-wall rated jacket means keeping cable clutter off the floor while safely running it through the wall. Commercial-grade connectors that feature compact overmolding for high-density environments, integrated finger grips on the top, bottom, and sides for easy insertion and removal. The gripping connector shells have 2x port retention to keep your devices connected. The gold-plated connectors on the cables allow for better shielding, increased electrical conductivity, and durability.

These cables have also been tested and certified to ensure low EMI to reduce the possibility of interference with wireless networks, streaming media players, Bluetooth devices, and mobile phones. Lastly, this tested and certified ultra high speed cable is backed by a lifetime warranty.

Features & Benefits

Tested to conform with the Ultra High Speed HDMI Cable Certification Program to ensure quality and support for all HDMI 2.1 features	Supports 8K 60Hz, 4K 120Hz, and 10K resolutions and refresh rates for immersive viewing
Bandwidth up to 48Gbps to support ultra high speed features	Dynamic HDR for greater image detail
Enhanced Audio Return Channel (eARC), which supports the latest audio formats	In-wall (CMG/FT4) rated jacket, so you can safely run the cable inside of a wall and have a clutter free, clean look
Integrated finger grips on the connectors for easy insertion and removal	Gripping connector shell for 2x greater port retention
New Ultra High Speed Cable type, backward compatible with earlier HDMI specifications	Exceptionally low EMI (electro-magnetic interference), which reduces interference with nearby wireless devices
Backed by a Lifetime Warranty for peace of mind	

Specifications

General Info

Product Line	C2G	Color	Black
--------------	-----	-------	-------

UPC Number	757120104537	Country Of Origin	China
------------	--------------	-------------------	-------

Application Sector	Residential, Commercial	Type	Cable
--------------------	-------------------------	------	-------

Dimensions

Cable Length	3 ft
--------------	------

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
-----------------	--------------------------	------------	--------

Video Resolution	10K, 8K 60Hz, 8K 30Hz, 8K, 4K 120Hz, 4K 60Hz, 4K 30Hz, 4K, 1080p	Bend Radius	48 mm
------------------	--	-------------	-------

Cable Type	Video, Ultra High Speed HDMI	Jacket Rating	CMG (FT4) Rated
------------	------------------------------	---------------	-----------------

Data Transfer Rate	48 Gbps	Adapter Rear	HDMI Male
--------------------	---------	--------------	-----------

Adapter Front	HDMI Male	Operating Temperature	-20 C, 75 C
---------------	-----------	-----------------------	-------------

Storage Temperature	-10 C, 55 C
---------------------	-------------
