



This USB-C to DisplayPort Adapter Converter is ideal for showing presentations, pictures, or other audio/video content from the USB-C port of a laptop or tablet to the DisplayPort input of a monitor, projector, or HDTV. This adapter supports up to a 4K (3840 x 2160) at 60Hz resolution, allowing it to deliver a high-quality video image to the connected display. The compact design of this adapter makes it perfect for BYOD (Bring Your Own Device) applications in education or corporate environments. This adapter is an ideal accessory for Apple® and other leading laptops and tablets.

Features and Benefits

- Supports resolutions up to 4K (3840 x 2160) at 60Hz
- Compatible with USB-C, Thunderbolt™ 3 and Thunderbolt™ 4 ports
- A reversible, symmetrical USB-C connector
- Compact, lightweight design
- Plug and Play—no driver required
- Compatible with the Apple® MacBook®, MacBook Air®, and MacBook Pro®

Features & Benefits

Supports resolutions up to 4K (3840 x 2160) at 60Hz

Compatible with USB-C, Thunderbolt™ 3 and Thunderbolt™ 4 ports

A reversible, symmetrical USB-C connector

Compact, lightweight design

Plug and Play—no driver required

Compatible with the Apple® MacBook®, MacBook Air®, and MacBook Pro®

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120269335	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Adapter		

Dimensions

Product Width US	1.5 in	Product Height US	0.6 in
------------------	--------	-------------------	--------

Product Length US	1.65 in	Cable Length	4.7 in
Listing Agencies / 3rd Party Agencies			
CE Certified	Yes	FCC Compliant	Yes
Technical Information			
Jacket Material	PVC (Polyvinyl Chloride)	Video Resolution	4K 60Hz
Storage Humidity	15-85% RH	Bend Radius	40 mm
Thickness	4 mm	Cable Type	Adapter
Jacket Rating	VW-1	Cable Diameter	4 mm
Connector 2	DisplayPort Female	Connector 1	USB-C Male
Video Output Support	DisplayPort	Operating Temperature	0°-50°C
Operating Humidity	15-85% RH	Video Input Support	USB-C
Voltage	0 to 30 V	Storage Temperature	-10° - 70° C