



This USB-C to HDMI Audio/Video Adapter Converter is an ideal solution for connecting a device with a USB-C port to an HDTV, projector, or other display with an HDMI port. This adapter supports up to a 4k (3840 x 2160) at 60Hz resolution, allowing it to deliver a high-quality video image to the connected display. The compact design of this adapter makes it a perfect pair for BYOD (Bring Your Own Device) applications in education or corporate environments. This adapter is an ideal accessory for Apple® and other leading laptops and tablets.

#### Features and Benefits

- Supports resolutions up to 4K (3840 x 2160) at 60Hz
- Compatible with USB-C, Thunderbolt™ 3 and Thunderbolt™ 4 ports
- A reversible, symmetrical USB-C connector
- Compact, lightweight design
- Plug and Play—no driver required
- Compatible with the Apple® MacBook®, MacBook Air®, and MacBook Pro®

## Features & Benefits

Supports resolutions up to 4K (3840 x 2160) at 60Hz	Compatible with USB-C, Thunderbolt™ 3 and Thunderbolt™ 4 ports
A reversible, symmetrical USB-C connector	Compact, lightweight design
Plug and Play, no driver required	Compatible with the Apple® MacBook®, MacBook Air®, and MacBook Pro®

## Specifications

### General Info

Product Line	C2G	Color	White
UPC Number	757120269366	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Adapter		

### Dimensions

Product Width US	1.5 in	Product Height US	0.6 in
------------------	--------	-------------------	--------

Product Length US	1.65 in	Cable Length	4.2 in
-------------------	---------	--------------	--------

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
--------------	-----	---------------	-----

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Video Resolution	4K 60Hz
Storage Humidity	15-85% RH (Non-Condensing)	Bend Radius	40 mm
Number of Ports	1	Thickness	4 mm
Cable Type	Adapter	Jacket Rating	VW-1
Cable Diameter	4 mm	Connector 2	HDMI Female
Connector 1	USB-C Male	Video Output Support	HDMI
Operating Temperature	0°-45°C	Operating Humidity	15-85% RH (Non-Condensing)
Video Input Support	USB-C	Voltage	0 to 30 V
Storage Temperature	-10° - 70° C		