



The USB-A Male to Lightning Male Sync and Charging Cable is perfect as a replacement or a spare cable for syncing data and charging Lightning devices while at home, in the office, or on the go. This cable is compatible with all devices equipped with a Lightning port, including iPhones, iPads, iPods, AirPods, the Apple Pencil, Siri Remote for Apple TV, Magic Mouse, Magic Keyboard, Magic Trackpad, and many third-party accessories. The Lightning adapter has a simple-to-use, reversible, symmetrical design, and the cable construction makes it ideal for travel. This cable has an MFi certified rating approved by Apple, meaning it is safe to use, protecting your Apple device from potential damage or harm that could come from using a non-certified accessory cable.

Additional Technical Specs

Electrical Specification

- Nominal Impedance: 100Ω
- Nominal Capacitance: 95.2 pF/m
- Insulation Resistance: 10MΩ
- Recognition Resistance 2.1A Voltage Test: D+2.7±0.1V, D-2.0±0.1V
- Non-Load/Load 2.1A Voltage Test: 4.40V~5.25V

Physical Characteristics

- USB Connector: USB-A Male, Nickel Plated
- Lightning Connector: Lightning Male, Nickel Plated
- Jacket: White PVC
- Cable OD: 3.0mm
- Product is CE Marked and MFi Certified

Features & Benefits

- Convenient syncing and charging capabilities through a computer's USB-A port
- Compatibility with devices equipped with Lightning ports
- Lightning adapter provides a reversible design, which is identical on both sides
- MFi certified and approved by Apple to be safe and compatible with Apple devices

Specifications

General Info

Product Line	C2G	Color	White
UPC Number	757120299059	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Cable

Dimensions

Product Length US	3.0 FT	Cable Length	3 ft
-------------------	--------	--------------	------

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
--------------	-----	---------------	-----

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Storage Humidity	15-85% RH (Non-Condensing)
Bend Radius	15 mm	Conductor Stranding	Stranded
Cable Type	USB	Cable Diameter	3 mm
Connector 2	Lightning Male	Connector 1	USB-A Male
Impedance	100 Ohm	Operating Temperature	0°-45°C
Operating Humidity	15-85% RH (Non-Condensing)	Storage Temperature	0° - 75° C
