



The USB-A Male to Lightning Male Sync and Charging Cable is perfect as a replacement or a spare cable for syncing data and charging Lightning devices while at home, in the office, or on the go. This cable is compatible with all devices equipped with a Lightning port, including iPhones, iPads, iPods, AirPods, the Apple Pencil, Siri Remote for Apple TV, Magic Mouse, Magic Keyboard, Magic Trackpad, and many third-party accessories. The Lightning adapter has a simple-to-use, reversible, symmetrical design, and the cable construction makes it ideal for travel. This cable has an MFi certified rating approved by Apple, meaning it is safe to use, protecting your Apple device from potential damage or harm that could come from using a non-certified accessory cable.

Additional Technical Specs

Electrical Specification

- Nominal Impedance: 100Ω
- Nominal Capacitance: 95.2 pF/m
- Insulation Resistance: 10MΩ
- Recognition Resistance 2.1A Voltage Test: D+2.7±0.1V, D-2.0±0.1V
- Non-Load/Load 2.1A Voltage Test: 4.40V~5.25V

Physical Characteristics

- USB Connector: USB-A Male, Nickel Plated
- Lightning Connector: Lightning Male, Nickel Plated
- Jacket: White PVC
- Cable OD: 3.0mm
- Product is CE Marked and MFi Certified

Features & Benefits

Convenient syncing and charging capabilities through a computer's USB-A port

Compatibility with devices equipped with Lightning ports

Lightning adapter provides a reversible design, which is identical on both sides

MFi certified and approved by Apple to be safe and compatible with Apple devices

Specifications

General Info

Product Line	C2G	Color	White
UPC Number	757120299073	Country Of Origin	China
Application Sector	Residential, Commercial	Type	Cable

Dimensions

Cable Length	10 ft
--------------	-------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Bend Radius	3 mm
-----------------	--------------------------	-------------	------

Cable Type	USB	Adapter Rear	Lightning Male
------------	-----	--------------	----------------

Adapter Front	USB-A Male	Impedance	100 ohms
---------------	------------	-----------	----------
