

HDMI® HDBaseT + USB-B and RS232 over Cat Extender Single Gang Wall Plate Transmitter to Box Receiver - 4K 60Hz allows a 4K HDMI source to be extended up to 130ft to a 4K display using a single Cat6a Ethernet cable. This is an ideal solution where USB must also be extended alongside HDMI video and audio to interactive whiteboards and displays in conference rooms, classrooms, lecture halls, and many other installation needs far beyond the length limitations of standard HDMI cabling.

This HDBaseT kit extends HDMI and high speed USB 2.0 over a single Cat5e, Cat6, or Cat6a network patch cable. Extend 4K HDMI up to 115 feet and 1080p up to 230 feet using a Cat5e or Cat6 cable. For longer 4K distances, extend 4K HDMI up to 130 feet using a Cat6a cable. Extend USB 2.0 pass through up to 230ft, connecting up to 4 USB devices to the receiver.



This kit is HDCP 2.2 compliant, making sure that the connection from the source is secure. Multi-channel audio formats are supported, including PCM 2.0/5.1/7.1, Dolby TrueHD, Dolby Atmos, DTS-HD Master Audio, and DTS:X. High speed USB 2.0 pass-through supports up to 230ft for KVM control of devices such as USB cameras, keyboards, mice, etc. With one-way Power over HDBaseT (PoH) support, the transmitter gets its power from the receiver, so no additional power adapter is required, allowing for greater installation flexibility. Advanced users can control RS232 pass-through to pass RS232 commands between the wall plate and the receiver. The receiver toggle switch also allows for the selection of upgrades that can upgrade both the wall plate and receiver.

Note: Ensure a solid, reliable connection between the 4K HDMI HDBaseT Extender and critical equipment. We suggest using HDMI Cables with gripping connectors that provide greater port retention than standard HDMI connectors.

Note: Stranded Cat5e/6/6a patch cables may be used for HDMI extension applications up to 230ft. Shielded, solid conductor Cat6 or HDBaseT Certified Cat6a network cabling is recommended for applications where the category cable must be coiled, is run near other high-frequency signaling cables, or in high EMI/RFI environments. For best performance use an [HDBaseT Certified Cat6a Patch Cable](#).

Features & Benefits

- Extend 4K at 60Hz (4:4:4) up to 130ft and 1080p at 60Hz up to 230ft with Cat 6a cable
- HDCP 2.2 compliant, to create a secure connection between the source and display
- Supports EDID from the HDMI out
- Supports USB 2.0 pass through over HDBT up to 230ft, connecting up to 4 USB devices to the receiver
- RS232 pass through mode can pass the RS232 command between wall plate and receiver
- Upgrade mode can update both wall plate and receiver
- Extend 4K at 60Hz (4:4:4) up to 115ft and 1080p at 60Hz up to 200ft with Cat 5e/6 cable
- Supports multi-channel audio formats, including PCM 2.0/5.1/7.1, Dolby TrueHD, Dolby Atmos, DTS-HD Master Audio and DTS:X
- Supports CEC pass-through, allowing central control to all HDMI compatible devices
- Supports one-way Power over HDBaseT (PoH), so that the wall plate can be powered by receiver
- Toggle Switch (receiver only) used to select RS232 port function - RS232 pass through or upgrade

Specifications

General Info

| | | | |
|-------------------|----------------------|--------------------|-------------------------|
| Product Line | C2G | UPC Number | 757120300243 |
| Country Of Origin | China | Application Sector | Residential, Commercial |
| Type | HDBaseT, Transmitter | | |

Additional Information

Prop 65 Warning Required Yes Prop 65 Warning Language Cancer and Reproductive Harm

Technical Information

| | | | |
|---------------------|---|-----------------------|---|
| Jacket Material | PVC (Polyvinyl Chloride) | Video Resolution | 4K 60Hz, 4K 30Hz, 4K, 1080p 60Hz, 1080p |
| Data Transfer Rate | 18 Gbps | Adapter Rear | DC Power Plug, RJ45 Female, HDMI Female, USB-A Female, USB-A Female, USB-A Female, USB-A Female |
| Adapter Front | DC Power Plug, RJ45 Female, HDMI Female, USB-B Female | Operating Temperature | 0 C, 45 C |
| Storage Temperature | -20 C, 70 C | | |
