

This USB-A to USB-C Dongle Adapter Converter for AV Ring is an easy and convenient solution for connecting a USB-C cable, USB-C hub, or USB-C peripherals to a USB-A female port on a laptop or source device. The eyelet hole on the adapter makes it a perfect addition to your new or existing HDMI AV Adapter Ring.

Pair this adapter with a USB-A laptop and the Barco ClickShare to enjoy a hybrid meeting space with flexibility for virtual collaboration.

Easily attach this USB-A to USB-C Dongle Adapter to any of our [HDMI Adapter Rings](#).

Note: This USB-A to USB-C Adapter supports USB 2.0 (480 Mbps) and will not support video transmission.

Features and Benefits:

- Adapts a USB-A female port of a laptop or source device to a USB-C port for data transmission
- Dongle style adapter reduces strain, prolonging the life of the port
- Plug-and-play, so no additional software or drivers needed
- Adapter includes a blue band around it, making it quickly identifiable when added to an HDMI AV Adapter Ring



Additional Technical Specifications

SIGNAL SPECIFICATIONS

- Testing: 100% Functional Test @ USB 2.0 (480 Mbps)

ELECTRICAL SPECIFICATIONS

- Conductor Resistance: at 20°C Max, 28 AWG: 237Ω/KM; 24 AWG: 93Ω/KM
- Voltage Rating: 30V
- Insulation Resistance: 10 Ω/KM min at 20°C DC 500V
- Dielectric Strength: AC 500V/1 Minute No Breakdown

PHYSICAL SPECIFICATIONS

- Temperature Rating: 105°C
- Minimum Bend Radius: 25mm

PHYSICAL CHARACTERISTICS

- Connector 1: USB-A Male; Solder Type, Contacts: Brass, Gold Flash, Housing: PBT, White, Shell: Nickel Plated
- Connector 2: USB-C Female; Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black, Shell: Nickel Plated
- Adapter Hood: Molded Black (Pantone/#Black 6C) PVC
- Color Band: Blue (Pantone#801C)
- Jacket Material: PVC
- Jacket Thickness: 0.55mm AVG
- Product is CE Marked and Conforms to 2011/65/EU ROHS 2

Features & Benefits

Adapts a USB-A female port of a laptop or source device to a USB-C port for data transmission	Dongle style adapter reduces strain, prolonging the life of the port
Plug-and-play, so no additional software or drivers needed	Adapter includes a blue band around it, making it quickly identifiable when added to an HDMI AV Adapter Ring

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120300618	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Active Device, Adapter, Converter

Dimensions

Product Length US	6.4 in
-------------------	--------

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
REACH Compliant	Yes		

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Bend Radius	25 mm
Jacket Rating	FT1 Rated, VW-1 Rated	Data Transfer Rate	480 Mbps
Connector 2	USB-A Male	Connector 1	USB-C Female
Voltage	30.0 V		