

This USB-A to USB-C Dongle Adapter Converter is an easy and convenient solution for connecting a USB-C cable, USB-C hub, or USB-C peripherals to a USB-A female port on a laptop or source device.

Pair this adapter with a USB-A laptop and the Barco ClickShare to enjoy a hybrid meeting space with flexibility for virtual collaboration.

**Note:** This USB-A to USB-C Adapter supports USB 2.0 (480 Mbps) and will not support video transmission.

#### Features and Benefits:

- Adapts a USB-A female port of a laptop or source device to a USB-C port for data transmission
- Dongle style adapter reduces strain, prolonging the life of the port
- Plug-and-play, so no additional software or drivers needed

#### Additional Technical Specifications

##### SIGNAL SPECIFICATIONS

- Testing: 100% Functional Test @ USB 2.0 (480 Mbps)

##### ELECTRICAL SPECIFICATIONS

- Conductor Resistance: at 20°C Max, 28 AWG: 237Ω/KM; 24 AWG: 93Ω/KM
- Voltage Rating: 30V
- Insulation Resistance: 10 Ω/KM min at 20°C DC 500V
- Dielectric Strength: AC 500V/1 Minute No Breakdown

##### PHYSICAL SPECIFICATIONS

- Temperature Rating: 105°C
- Minimum Bend Radius: 25mm

##### PHYSICAL CHARACTERISTICS

- Connector 1: USB-A Male; Solder Type, Contacts: Brass, Gold Flash, Housing: PBT, White, Shell: Nickel Plated
- Connector 2: USB-C Female; Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black, Shell: Nickel Plated
- Adapter Hood: Molded Black (Pantone/#Black 6C) PVC
- Color Band: Black (Pantone#6C)
- Jacket Material: PVC
- Jacket Thickness: 0.55mm AVG
- Product is CE Marked and Conforms to 2011/65/EU ROHS 2



## Features & Benefits

Adapts a USB-A female port of a laptop or source device to a USB-C port for data transmission

Dongle style adapter reduces strain, prolonging the life of the port

Plug-and-play, so no additional software or drivers needed

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120300625	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	5-Year
Type	Active Device, Adapter, Converter		

Dimensions

Product Length US	6.4 in
-------------------	--------

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
REACH Compliant	Yes		

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Bend Radius	25 mm
Jacket Rating	FT1 Rated, VW-1 Rated	Data Transfer Rate	480 Mbps
Connector 2	USB-A Male	Connector 1	USB-C Male
Voltage	30.0 V		