

This Micro HDMI to HDMI Dongle Adapter is a great addition to your existing HDMI Adapter Ring — an easy and convenient solution for connecting a micro HDMI port to an HDMI enabled device in your home or office. This adapter carries a digital video signal, supporting up to a 4K resolution and meets the requirements for high performance applications.

Avoid frustration by simply plugging the adapter into your computer, then attach it to the existing HDMI cable from your monitor or projector. The portable, compact design also makes it easy to carry in a laptop bag when traveling or on the go.

Easily attach this Micro HDMI Dongle Adapter to any of the following [HDMI Adapter Rings](#).

Additional Technical Specifications

SIGNAL SPECIFICATIONS

- Testing: 100% Functional Test at 4K/30Hz

ELECTRICAL SPECIFICATIONS

- Conductor Resistance: at 20°C, 32AWG: 588Ω/KM; 34AWG: 959Ω/KM
- Voltage Rating: 30V
- Insulation Resistance: 10 Ω/KM min at 20°C DC 500V
- Dielectric Strength: AC 500V/1 Minute No Breakdown

PHYSICAL SPECIFICATIONS

- Temperature Rating: 80°C
- Minimum Bend Radius: 25mm (about 0.98 in)
- Cable Jacket Rating: VW-1
- Tensile Strength: Unaged: 1500psi; Aged: 70% min.

PHYSICAL CHARACTERISTICS

- Connector 1: HDMI Female; Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black, Shell: Nickel Plated
- Connector 2: micro HDMI; Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black, Shell: Nickel Plated
- Adapter Hood: Molded Black (Pantone/#Black 6C) PVC
- Color Band: Orange; 12 x 1.5mm (about 0.06 in)
- Jacket Material: PVC
- Jacket Thickness: 0.51mm (about 0.02 in) AVG
- Product is CE Marked and Conforms to 2011/65/EU ROHS 2



Features & Benefits

Adapts a micro HDMI output to HDMI,
so no need to purchase a new monitor

Dongle style adapter reduces strain, prolonging the life of the port

Plug and play, so no additional
software or drivers needed

Adapter supports up to a 4K video resolution, so meeting attendees will be able to see
the displayed content for improved comprehension and detailed decision making

Specifications

General Info

| | | | |
|--------------------|-----------------------------------|-------------------|--------|
| Product Line | C2G | Color | Black |
| UPC Number | 757120300687 | Country Of Origin | China |
| Application Sector | Commercial, Residential | Warranty Type | 5-Year |
| Type | Active Device, Adapter, Converter | | |

Dimensions

| | | | |
|-------------------|---------|--------------|---------|
| Product Length US | 0.25 FT | Cable Length | 0.25 ft |
|-------------------|---------|--------------|---------|

Listing Agencies / 3rd Party Agencies

| | | | |
|-----------------|-----|---------------|-----|
| CE Certified | Yes | FCC Compliant | Yes |
| REACH Compliant | Yes | | |

Technical Information

| | | | |
|-----------------|--------------------------|------------------|-----------------------|
| Jacket Material | PVC (Polyvinyl Chloride) | Video Resolution | 1080p, 4K, 4K 30Hz |
| Bend Radius | 25 mm | Jacket Rating | FT1 Rated, VW-1 Rated |
| Cable Diameter | 4.5 mm | Adapter Rear | HDMI Female |
| Adapter Front | HDMI Micro Male | Voltage | 30 V |