



**C2G**  
**Discontinued - Cisco® GLC-SX-MM Compatible 1000Base-SX SFP (mini-GBIC) Transceiver Module (Multimode, 850nm, LC) - 5-Pack**  
Part No. CG-GLC-SX-MM-LEG-5PK

Customers are encouraged to migrate to new Cisco compatible Gigabit Ethernet SFP transceiver modules: [L path="https://www.cablestogo.com/product/GLC-SX-MMD-LEG"]GLC-SX-MMD-LEG[/L]



This SFP (mini-GBIC) transceiver module is designed for use with Cisco network equipment and is equivalent to Cisco part number GLC-SX-MM. This transceiver is built to meet or exceed the specifications of the OEM and to comply with Multi-Source Agreement (MSA) standards. This product is 100% functionally tested, and compatibility is guaranteed. The transceiver is hot-swappable input/output device which allows a Gigabit Ethernet port to link with a fiber optic network. OEM specific configuration data is loaded on to the EEPROM of the transceiver at the factory, allowing this transceiver to initialize and perform identically to an OEM transceiver. This transceiver may be mixed and deployed with other OEM or third party transceivers and will deliver seamless network performance. A list of compatible network equipment is available on the Specs tab of this page.

[B]Please Note:[/B] Installing Legrand transceivers does not void your network equipment warranty. Network equipment manufacturers all have guidelines stating that warranty support on their products will not be affected by installing a Legrand or any third party transceiver.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco Systems, Inc. This product is not certified or endorsed by Cisco Systems

## Features & Benefits

Functionally identical to Cisco GLC-SX-MM

850nm wavelength signaling

LC ports designed for use with Multimode Fiber

Supports up to 550 meters of cabling

## Specifications

### General Info

Product Line	C2G	Color	Silver
UPC Number	757120667063	Application Sector	Commercial, Industrial
Type	Transceiver		

### Technical Information

Fiber Optic Cable Type	Multimode	Max Distance Support	550 m
Connector 2	LC Female, LC Female	Connector 1	SFP Male