



C2G

DISCONTINUED: Rack PDU, Basic, Zero U, 12A, 120V, (14) 5-20R, 5-15P Cord

Part No. CG-LP-21100

Basic PDUs provide reliability and simple installation. Standardized power distribution enables cost effective scaling, speed to deployment, and simplifies procurement due to a common platform.



Features & Benefits

Input Plug: NEMA 5-15P

Output Receptacles: (14) NEMA 5-20R, 16A

Integrated Locking Outlets on IEC Receptacles: Eliminates the need for special power cords that lock at the PDU

Rotatable Cord: Enables maximum flexibility for routing the input plug—simplifying the installation of Zero U PDUs

Mounting Types: Available in horizontal and vertical configurations to ensure power distribution is optimally located

Hydraulic-Magnetic Breakers: Provide less heat dependent local protection and quick recovery from circuit overload, by utilizing a two-step response curve—these breakers provide a delay on normal overcurrents, while tripping quickly on short circuits

Specifications

General Info

Product Line	C2G	UPC Number	662875014904
Country Of Origin	China	Number of Receptacles	14
Application Sector	Commercial, Industrial	Warranty Type	2-Year
Type	PDU		

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Rack Units

0U

Voltage

100 V, 120 V
