



Network Metered PDUs enable line level power metering in real time. Allowing remote monitoring of the load level, custom notifications, and user specified conditions. Each Network Metered PDU provides visibility and reporting of power usage on the PDUs Color LCD screen and to tablets, smart phones, or computers from nearly anywhere.

Features & Benefits

- Input Plug: NEMA L6-20P

Rotatable Cord: Enables maximum flexibility for routing the input plug—simplifying the installation of Zero U PDUs

Hydraulic-Magnetic Breakers: Provide less heat dependent local protection and quick recovery from circuit overload, by utilizing a two-step response curve—these breakers provide a delay on normal overcurrents, while tripping quickly on short circuits

- Output Receptacles: (8) Locking IEC-C13, 12A

Mounting Types: Available in horizontal and vertical configurations to ensure power distribution is optimally located

Specifications

General Info

Product Line	C2G	UPC Number	662875019893
Country Of Origin	Taiwan, Province Of China	Number of Receptacles	8
Application Sector	Commercial, Industrial	Type	PDU

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Rack Units	1U	Voltage	200 V, 240 V
------------	----	---------	--------------