



C2G
Rack PDU, Network Metered, Zero U, 24A, 208V, (36) C13 & (6) C19, L6-30P Cord
Part No. CG-LP-42300



Network Metered PDUs enable line level power metering in real time. Allowing remote monitoring of the load level, custom notifications, and user specified conditions. Each Network Metered PDU provides visibility and reporting of power usage on the PDUs Color LCD screen and to tablets, smart phones, or computers from nearly anywhere.

Features & Benefits

Input Plug: NEMA L6-30P

Output Receptacles: (36) Non-Locking IEC-C13, 12A- (6) Non-Locking IEC-C19, 16A

Integrated Locking Outlets on IEC Receptacles: Eliminates the need for special power cords that lock at the PDU

Rotatable Cord: Enables maximum flexibility for routing the input plug—simplifying the installation of Zero U PDUs

Mounting Types: Available in horizontal and vertical configurations to ensure power distribution is optimally located

Hydraulic-Magnetic Breakers: Provide less heat dependent local protection and quick recovery from circuit overload, by utilizing a two-step response curve—these breakers provide a delay on normal overcurrents, while tripping quickly on short circuits

Specifications

General Info

Product Line	C2G	UPC Number	662875015253
Country Of Origin	Taiwan, Province Of China	Number of Receptacles	36
Application Sector	Commercial, Industrial	Type	PDU

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Rack Units	0U	Voltage	200 V, 240 V
------------	----	---------	--------------