



Distribute, manage, and control power to connected equipment, enabling load monitoring, individual outlet power cycling, and power sequencing. This control can be accessed locally or remotely, multiplying the reach and ability of IT staff and caretakers. A single portal view provides visibility and control of power usage and available capacity, which simplifies the maintenance responsibilities of taxed IT departments.

## Features & Benefits

Input Plug: NEMA L5-30P

Output Receptacles: (24) NEMA 5-20R, 16A

Networked Controller: Enables remote and local monitoring and control of the PDU and peripherals

Circuit Breaker Trip Detection / Alerting: Get notification instantly in the instance of a tripped circuit breaker

Delayed Power Sequencing: Sequence the order in which each outlet is turned on or off to avoid dropped power loads or circuit overloading

Outlet Use Management: From the PDU GUI, you can remotely identify named outlets and if an outlet is on or off

## Specifications

### General Info

Product Line	C2G	UPC Number	662875015598
Country Of Origin	Taiwan, Province Of China	Number of Receptacles	24
Application Sector	Commercial, Industrial	Warranty Type	2-Year
Type	PDU		

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

Rack Units	0U	Voltage	100 V, 120 V
------------	----	---------	--------------